GROUT AND SILICONE

ARDEX SE SILICONE

Coloured Silicone for Sanitary Installations

ARDEX SE is an acetic cure sealant for applications such as movement joints (between tiles), internal corners (tiled wall and floor) and connecting joints between tiled surface and benchtops, bath edges, cupboards, splashbacks. LOW VOC

JOINT WIDTH

Max width 30mm, depth 15mm

SUITABILITY

ARDEX SE bonds well to ceramic tiles, glass, enamel, anodized aluminium, granite, porcelain, laminated bench tops and sanitary acrylics. (Not recommended for other natural stones, e.g. marble, travertine and limestones. May cause discoloration to brass and copper).

LOCATION

Internal, External Use ARDEX ST as bond breaker when using with ARDEX waterproof membranes (Not suitable for continuous immersion use e.g. swimming pools)

SURFACES

Floors, Walls

COLOURS

See ARDEX Website for Colour Selection.

COVERAGE

Approximately 12 lineal metres per cartridge with a 5 x 5mm joint size

PACKAGING

210ml contridan

Travertine	Alabaster	Midnight	Havana	Mudberry
Slate Grey	Todd River Sand	Buff	Olive	Macchiato
Ultra White	Charred Ash	Misty Grey	Magellan Grey	
ADAL	CONTACT US 1300 788 780 www.ardexau	ustralia.com		SYSTEM ARDEX
	Download on the ANDROD APPON ADD Store	Download the Ardex ap		PREMIUM PERFORMANCE



ARDEX SE **QUICK FACTS**

- Flexible sealant for use in tile movement and connecting joints
- Colour matched to popular grout and sanitary ware
- Elastic withstands 25% total movement of original ioint width