UV-SPEC and UV-SPEC TRAFFIC

Waterproof Membranes Australia

Chemwatch: **5410-07** Version No: **3.1.1.1**

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 29/06/2020 Print Date: 29/06/2020 S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	UV-SPEC and UV-SPEC TRAFFIC
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Water Proof Membrane.

Use according to manufacturer's directions.

Details of the supplier of the safety data sheet

Registered company name	Waterproof Membranes Australia		
Address	02/ 123-129 Dolphin St Coogee NSW 2034 Australia		
Telephone	(02) 9079 0872		
Fax	Not Available		
Website	www.wmaustralia.com.au		
Email	sales@bocagroup.com.au		

Emergency telephone number

Association / Organisation	Poison Information Centre
Emergency telephone numbers	13 11 26
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable			
Classification [1]	in Corrosion/Irritation Category 2, Eye Irritation Category 2A			
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI			





SIGNAL WORD WARNING

Hazard statement(s)

Label elements

H315	Causes skin irritation.
H319	Causes serious eye irritation.

Precautionary statement(s) Prevention

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

	•
P321	Specific treatment (see advice on this label).
P362	Take off contaminated clothing and wash before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water.

Issue Date: 29/06/2020 Print Date: 29/06/2020

P332+P313

If skin irritation occurs: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
1317-65-3	10-<20	limestone	
Not Available	balance	Ingredients determined not to be hazardous	
Not Available		include	
9065-11-6	>60	acrylic resin	
7732-18-5	10-20	water	

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Number Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ► Water spray or fog.
- Foam.
- ► Dry chemical powder.
- BCF (where regulations permit).

Fire/Explosion Hazard

Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result Advice for firefighters Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area. Fire Fighting Avoid spraying water onto liquid pools. ▶ DO NOT approach containers suspected to be hot.

- ▶ Cool fire exposed containers with water spray from a protected location.

▶ Combustible.

- If safe to do so, remove containers from path of fire.
- ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.
- ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).
- ► May emit acrid smoke.
- ▶ Mists containing combustible materials may be explosive

Combustion products include:

carbon dioxide (CO2)

Chemwatch: 5410-07 Version No: 3.1.1.1

Page 3 of 9 **UV-SPEC and UV-SPEC TRAFFIC**

Issue Date: 29/06/2020 Print Date: 29/06/2020

other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.

HAZCHEM

Not Applicable

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Mathada and material for containment and alcaning un

Methods and material for conta	ainment and cleaning up
Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

- ▶ Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area.
- ▶ Prevent concentration in hollows and sumps.
- ▶ DO NOT enter confined spaces until atmosphere has been checked.
- ▶ DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials. Safe handling
 - ► When handling, **DO NOT** eat, drink or smoke
 - ▶ Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.
 - ▶ Use good occupational work practice.
 - ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Other information

- Store in original containers. Keep containers securely sealed.
- ▶ No smoking, naked lights or ignition sources.
- ▶ Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container

PP Plastic pails (15 Litres)

Storage incompatibility

- $\mbox{\ensuremath{\,^{\blacktriangleright}}}$ Avoid reaction with oxidising agents, bases and strong reducing agents.
- Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.















Must not be stored together

- May be stored together with specific preventions
- May be stored together

Chemwatch: 5410-07 Page 4 of 9

UV-SPEC and UV-SPEC TRAFFIC

Issue Date: 29/06/2020 Print Date: 29/06/2020

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Version No: 3.1.1.1

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	limestone	Calcium carbonate	10 mg/m3	Not Available	Not Available	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.

EMERGENCY LIMITS

Ingredient	Material name TEEL-1			TEEL-2	TEEL-3	
limestone	Carbonic acid, calcium salt	45 mg/m3		210 mg/m3	1,300 mg/m3	
Ingredient	Original IDLH			Revised IDLH		
limestone	Not Available		Not Available			

Ingredient	Original IDLH	Revised IDLH
limestone	Not Available	Not Available
acrylic resin	Not Available	Not Available
water	Not Available	Not Available

Exposure controls

Appropriate engineering controls

General exhaust is adequate under normal operating conditions.

Personal protection









- ► Safety glasses with side shields.
- Chemical goggles.

Eye and face protection

▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

See Hand protection below

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact.
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161,10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.

Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as:

- Excellent when breakthrough time > 480 min
- Good when breakthrough time > 20 min
- Fair when breakthrough time < 20 min
- Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Body protection

Hands/feet protection

See Other protection below

Chemwatch: **5410-07**Version No: **3.1.1.1**

UV-SPEC and UV-SPEC TRAFFIC

Issue Date: **29/06/2020**Print Date: **29/06/2020**

Other protection

- ▶ Overalls
- ▶ P.V.C apron.
- ▶ Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

UV-SPEC and UV-SPEC TRAFFIC

Material	СРІ
BUTYL	Α
NEOPRENE	Α
VITON	Α
NATURAL RUBBER	С
PVA	С

^{*} CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS	-	A-PAPR-AUS / Class 1
up to 50 x ES	-	A-AUS / Class 1	-
up to 100 x ES	-	A-2	A-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Light grey viscous liquid; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7

Version No: 3.1.1.1

Page 6 of 9 **UV-SPEC and UV-SPEC TRAFFIC**

Issue Date: 29/06/2020 Print Date: 29/06/2020

Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information	on	toxical	ogical	effects

formation on toxicological e	ffects		
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.		
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. High molecular weight material; on single acute exposure would be expected to pass through gastrointestinal tract with little change / absorption. Occasionally accumulation of the solid material within the alimentary tract may result in formation of a bezoar (concretion), producing discomfort.		
Skin Contact	This material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Eye	This material can cause eye irritation and damage in so	me persons.	
Chronic	Long-term exposure to the product is not thought to product models); nevertheless exposure by all routes should be		ealth (as classified by EC Directives using animal
	TOVICITY	IDDITATION	
UV-SPEC and UV-SPEC TRAFFIC	TOXICITY Not Available	IRRITATION	
TO THE STATE OF TH	Not Available	Not Available	
	TOXICITY	IRRITATION	
	Oral (rat) LD50: 6450 mg/kg ^[2]	Eye: no adverse e	effect observed (not irritating) ^[1]
limestone		Skin (rabbit): 500	mg/24h-moderate
		Skin: no adverse effect observed (not irritating) ^[1]	
	TOXICITY	IRRITATION	
acrylic resin	Not Available	Not Available	
	TOXICITY	IRRITATION	
water	Oral (rat) LD50: >90000 mg/kg ^[2] Not Available		
Legend:	Value obtained from Europe ECHA Registered Subst specified data extracted from RTECS - Register of Toxic		ned from manufacturer's SDS. Unless otherwise
LIMESTONE	Eye (rabbit) 0.75: mg/24h - No evidence of carcinogenic The material may produce severe irritation to the eye ca produce conjunctivitis. The material may cause skin irritation after prolonged or vesicles, scaling and thickening of the skin.	ausing pronounced inflammation. Rep	peated or prolonged exposure to irritants may
ACRYLIC RESIN	CAUTION: The chronic health effects of acrylic monomer. Use good occupational work practices to avoid personal		
ACRYLIC RESIN & WATER	No significant acute toxicological data identified in literat	ture search.	
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	~	Reproductivity	×
Serious Eye Damage/Irritation	~	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×

Legend:

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

Aspiration Hazard

SECTION 12 ECOLOGICAL INFORMATION

Mutagenicity

×

Toxicity

184 ODEO - 1184 ODEO	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
UV-SPEC and UV-SPEC TRAFFIC	Not Available	Not Available	Not Available	Not Available	Not Available

Chemwatch: **5410-07** Page **7** of **9**

Version No: 3.1.1.1

UV-SPEC and UV-SPEC TRAFFIC

Issue Date: **29/06/2020**Print Date: **29/06/2020**

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>56000mg/L	4
limestone	EC50	72	Algae or other aquatic plants	>14mg/L	2
	EC10	72	Algae or other aquatic plants	>14mg/L	2
	NOEC	72	Algae or other aquatic plants	14mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
acrylic resin	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
water	LC50	96	Fish	897.520mg/L	3
	EC50	96	Algae or other aquatic plants	8768.874mg/L	3
Legend:	V3.12 (QSAR) -	1. IUCLID Toxicity Data 2. Europe ECHA Reg Aquatic Toxicity Data (Estimated) 4. US EPA apan) - Bioconcentration Data 7. METI (Japai	, Ecotox database - Aquatic Toxicity Data 5.		

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ► Reduction
- ► Reuse
- ► Recycling
- ► Disposal (if all else fails)

Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Authority for disposal.
- ▶ Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

UV-SPEC and UV-SPEC TRAFFIC

Issue Date: **29/06/2020**Print Date: **29/06/2020**

Safety, health and environmental regulations / legislation specific for the substance or mixture

LIMESTONE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

ACRYLIC RESIN IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

Version No: 3.1.1.1

WATER IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

ECHA SUMMARY

Ingredient	CAS number	Index No	ECHA Dossier
limestone	1317-65-3	Not Available	01-2119486795-18-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Not Classified	Not Available	Not Available
1	Not Classified	Not Available	Not Available
1	Not Classified	Not Available	Not Available
1	Not Classified	Not Available	Not Available

 $Harmonisation \ \ Code\ 1 = The\ most\ prevalent\ classification.\ Harmonisation\ \ Code\ 2 = The\ most\ severe\ classification.$

Ingredient	CAS number	Index No	ECHA Dossier
acrylic resin	9065-11-6	Not Available	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Acute Tox. 4; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2; Acute Tox. 4	Wng	H302; H312; H315; H319; H332

 $Harmonisation \ Code \ 1 = The \ most \ prevalent \ classification. \ Harmonisation \ Code \ 2 = The \ most \ severe \ classification.$

Ingredient	CAS number	Index No	ECHA Dossier
water	7732-18-5	Not Available	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Not Classified	Not Available	Not Available

 $Harmonisation \ Code \ 1 = The \ most \ prevalent \ classification. \ Harmonisation \ Code \ 2 = The \ most \ severe \ classification.$

National Inventory Status

National Inventory	Status
Australia - AICS	No (acrylic resin)
Canada - DSL	No (acrylic resin)
Canada - NDSL	No (acrylic resin; water)
China - IECSC	No (acrylic resin)
Europe - EINEC / ELINCS / NLP	No (acrylic resin)
Japan - ENCS	No (acrylic resin)
Korea - KECI	No (acrylic resin)
New Zealand - NZIoC	No (acrylic resin)
Philippines - PICCS	No (acrylic resin)
USA - TSCA	No (acrylic resin)
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	No (acrylic resin)
Russia - ARIPS	No (acrylic resin)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	29/06/2020
Initial Date	26/06/2020

SDS Version Summary

Version	Issue Date	Sections Updated
3.1.1.1	29/06/2020	Classification, Supplier Information

Chemwatch: 5410-07 Page 9 of 9 Issue Date: 29/06/2020 Version No: 3.1.1.1 Print Date: 29/06/2020

UV-SPEC and UV-SPEC TRAFFIC

Other information

Ingredients with multiple cas numbers

Name	CAS No
acrylic resin	9065-11-6, 9900-07-6

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

 ${\sf PC-STEL} : {\sf Permissible\ Concentration-Short\ Term\ Exposure\ Limit}$

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.