5291 Manual DIN-Rail Thermostat







Manual control

Thermotouch manual thermostats offer an easy-to-operate manual mode, enabling you to have direct control over your Underfloor Heating system's temperature. This feature makes them a perfect choice for slab heating applications, especially when they are connected to off-peak power sources, as the thermostat operates exclusively during the off-peak periods.



Sensor Mode

The Thermotouch manual DIN-Rail Thermostat is supplied with a floor sensor and conduit.




Use with home automation

The 5291 Manual Thermostat features a temperature dial, it is designed to be mounted in your electrical box. The red light indicator shows when the heating is operating. The 5291 is floor sensing only.




WIRING DIAGRAM

- 1 220-240V AC Supply Live
- 2 220-240V AC Supply Neutral
- **4** UFH Live
- **5** UFH Neutral
- **6** Floor sensor (no polarity)
- Floor sensor (no polarity)



BOX CONTENTS

- 1 x Thermotouch DIN-Rail Thermostat
- 1 x Installation Guide
- 1 x 3m floor temperature sensor probe
- 1 x 2m sensor conduit



TECHNICAL DATA

Voltage	240V 50/60Hz
Maximum load	16Amps (3600W)
Class	
Warranty	3 years
IP rating	IP20
Width	36mm
Height	86mm
Depth	58mm (48mm in electrical board)
Complies	EN/BS 50 081-1, EN/BS 50 082-2,
	EN/BS 60 730-1 & EN/BS 70730-2-9

