

Ultra Mastik

LARGE FORMAT SUPERIOR TILE ADHESIVE

Description

Superior anti-slump properties means it can hold a 600 x 600mm tile on the wall without slipping. Excellent body and smooth feel without stickiness for easy trowelling. Suitable for commercial and high traffic installations.

AS ISO 13007 CLASSIFICATION

- C2 Improved Adhesive (excellent bond)
- S1 Flexible
- E Extended open time
- T Slip-resistant

Features

- Superb transfer means better contact coverage and less risk
- Simple installation of very large tiles with confidence
- Less tiler fatigue due to superb trowel feel
- Versatility means it can be used on most installations

Recommended Use

- Large tiles
- When superior non slump is needed
- Large jobs
- When one adhesive is needed for a variety of applications





Ultra Mastik

SUITABLE FOR			
Outdoor and Indoor	Wall and Floor		
Concrete	High Traffic		
Screed	Large Format		
Render	Porcelain		
Fibre Cement	Mosaic		
Plasterboard	Terracotta		
Bostik Approved Waterproofing Membranes	Moisture Stable Terrazzo and Natural Stone		

Suitable for use will all moisture stable tiles

COVERAGE			
When mixed bag yields 17 to 18 litres			
Approximate Coverage (10mm trowel)			
kg per m²	m² per bag		
2.80	7.0		

WORKING TIME					
POT LIFE	SETTING TIME	OPEN TIME			
3Hrs	<24hrs	>30min			

PRODUCT DETAILS					
ITEM NO	ITEM NAME	COLOUR	SIZE		
30840346	ULTRA MASTIK NSW	White	20Kg		
30840260	ULTRA MASTIK VIC	White	20Kg		
30840252	ULTRA MASTIK WA	White	20Kg		

IMPORTANT NOTES: This Sell Sheet is not intended as a replacement for the appropriate Technical Data Sheet. Always check the Packaging, Technical Data Sheet and MSDS before using. If there is any doubt contact Bostik before commencing work.



This document supersedes all previously published literature. April 2019

